

規格表(参考)

濾過面積 (m <sup>2</sup> )	濾過機本体							付帯機器						
	胴寸法(mm)		電動機(kW)		本体寸法(mm)			真空 ポンプ (kW)	濾液 ポンプ (kW)	プリコート ポンプ (kW)	濾液分離槽(mm)		プリコート槽(mm)	
	径	有効幅	胴	攪拌	幅	奥行	高さ				径	高さ	径	高さ
1	950	400	0.4	0.4	1,980	1,670	1,380	2.2	1.5	0.4	350	1,200	800	1,300
1.5	1,200	400	0.75	0.4	1,980	2,120	1,500	3.7	1.5	0.75	400	1,200	950	1,300
3	1,200	800	0.75	0.4	2,380	2,120	1,500	5.5	1.5	1.5	450	1,200	1,200	1,600
4.5	1,200	1,200	0.75	0.4	2,800	2,120	1,500	7.5	2.2	2.2	500	1,500	1,400	1,700
6	1,600	1,200	0.75	0.4	3,350	2,700	1,900	11	2.2	2.2	600	1,800	1,500	2,000
8	1,600	1,600	0.75	0.75	3,750	2,700	1,900	15	2.2	2.2	700	1,800	1,700	2,000
10	1,600	2,000	0.75	0.75	4,150	2,700	1,900	22	3.7	2.2	700	1,800	1,900	2,100
12.5	2,000	2,000	1.5	0.75	4,250	3,000	2,400	22	3.7	3.7	800	1,800	2,100	2,100
15	2,000	2,400	1.5	0.75	4,750	3,000	2,400	30	5.5	3.7	850	1,800	2,200	2,100
18	2,400	2,400	1.5	1.5	4,750	3,250	2,800	30	5.5	3.7	950	1,800	2,400	2,250
21	2,400	2,800	1.5	1.5	5,250	3,250	2,800	37	7.5	7.5	1,000	1,800	2,600	2,250
24.5	2,800	2,800	2.2	1.5	5,300	4,060	3,200	45	7.5	7.5	1,200	1,800	2,800	2,250
28	2,800	3,200	2.2	1.5	5,700	4,060	3,200	55	11	7.5	1,200	1,800	2,900	2,400
31.5	2,800	3,600	2.2	1.5	6,100	4,060	3,200	55	11	7.5	1,200	1,800	3,000	2,400
35	2,800	4,000	2.2	2.2	6,500	4,060	3,200	55	11	7.5	1,300	1,800	3,250	2,400
50	3,400	4,700	3.7	2.2	7,750	4,800	3,900	90	15	11	1,500	1,800	3,500	2,900
75	3,400	7,100	3.7	3.7	10,150	4,800	3,900	125	22	18.5	1,750	2,000	3,900	3,500
100	3,400	9,400	5.5	3.7	12,450	4,800	3,900	140	30	22	1,800	2,400	4,200	4,000

注) 濾過胴回転数は17~68rphを標準とします。