

## 規格表(参考)

機番	全容量 (ℓ)	本体寸法(mm)		据付寸法(mm)				回転数 (rpm)	電動機 (kW)	口径(mm)	
		直径(D)	高さ(A)	回転径(B)	芯高(C)	高さ(H)	長さ(L)			投入(E)	排出(O)
VTD100	100	550	815	1,100	900	1,400	2,400	15	0.75	200	150
VTD150	150	600	980	1,600	950	1,600	2,600	13	0.75	200	150
VTD250	250	740	1,085	1,650	1,000	1,650	3,000	11	1.5	300	150
VTD500	500	930	1,320	1,700	1,100	1,800	3,200	9	1.5	400	150
VTD1000	1,000	1,220	1,650	2,200	1,200	2,050	3,500	8	2.2	400	150
VTD1500	1,500	1,400	1,915	2,400	1,300	2,450	4,100	7	2.2	400	200
VTD2000	2,000	1,550	2,130	2,600	1,500	2,700	4,400	6	3.7	400	200
VTD2500	2,500	1,620	2,320	2,850	1,600	2,800	4,900	5.5	3.7~ 5.5	400	200
VTD3000	3,000	1,720	2,490	3,000	1,700	3,000	5,000	5	5.5~ 7.5	400	200
VTD5000	5,000	2,050	2,950	3,600	1,900	3,200	6,000	4.5	5.5~ 7.5	450	200
VTD7000	7,000	2,300	3,255	3,750	2,050	3,500	6,600	4	7.5~11	450	250
VTD10000	10,000	2,600	3,730	4,500	2,450	4,400	6,800	3.5	11 ~15	450	250
VTD15000	15,000	2,950	4,300	5,100	2,650	4,900	7,800	3.2	15 ~22	500	250
VTD20000	20,000	3,200	4,750	5,550	2,980	5,500	9,300	2.9	22 ~30	500	250

注) 仕込量は全容量に対して、真空吸引管固定型は50~60%、共同り型は35%前後が適当です。回転数は変速式も可能です。